

PWBAZ2 THE FLAT

Marking tool, fork guided.



Resilient marking tool



Marking wheel with segments Marking wheel with solid engraving

Field of application:

- Marking on even surfaces.

Types of machines:

- Suitable for all conventional and CNC controlled milling machines.

Properties:

- Marking system with return spring.

Tool:

- Special surface hardening allows for increased wear resistance of tool.

Marking wheels engraved from solid:

- Marking wheel dia-30mm, HSS, 4/401511-12. Max. type height 14mm (depending on material).
- Marking wheel dia-35mm, HSS, 4/402435. Max. type height 14mm (depending on material).
- Additional special marking wheels available on request.

Marking wheels for exchangeable segments:

- Marking wheels 4/401866R and 4/401866L for segments dia. 30mm. Max. type height 4mm.
- Marking wheels 4/402405R and 4/402405L for segments dia. 35mm. Max. type height 4mm.
- Additional special marking wheels for exchangeable segments available on request.

TOOL VARIANTS

Tool	Tool type	Execution	Straight shank size
PWBAZ2-16	PWBAZ2	Right	Ø 16mm
PWBAZ2-20	PWBAZ2	Right	Ø 20mm
PWBAZ2-25	PWBAZ2	Right	Ø 25mm

ITEM NUMBER SYSTEMATICS

PWBAZ2-20	PWBAZ2	-->	Tool type
	20	-->	Straight shank size 20mm

DIMENSION

